



## Performance

Continuous power (PRP)	300.0	(KVA)
Continuous power (PRP)	240.0	(KW)
Stand-by power (LTP)	330.0	(KVA)
Stand-by power (LTP)	264.0	(KW)
Power factor	0.8	

VOLTAGE		
Frequency (Hz)	50	Hz
Voltage (V)	400	V

DIMENSIONS AND NOISE LEVEL		
Width	1300	mm
Length	4000	mm
Height	2400	mm
Weight	3820	kg
Sound pressure 7 m.	73.0	dBA

## DATA REFERENCES

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0,850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.

**P.R.P. Prime Power-Continuous power at variable load:** The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer, according to ISO 8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.

**L.T.P. Limited-time running power-Limited power:** The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted.

*The data contained in this document is nominal and refers to the standard equipped model and is not binding. Psilos Services reserves the right to revise the information without notice per our policy of continuous product development and improvement.*



**GALAXY - F 301 GX**

## STRONG POINTS

1. Industrial diesel engine in genset version with certificate of origin.
2. Industrial brushless alternator with AVR.
3. Steel baseframe with retention basin and modular steel fuel tank with level sensor.
4. Soundproof canopy in galvanized, power coated sheet steel.
5. Soundproofing material made of high attenuation polyester fibre.
6. Internal exhaust silencer with insulated manifold.
7. Electrical panel mounted on board the unit with digital control device installed in metal box.
8. Compact for easy handling and use.
9. Test report, manuals and electrical drawings supplied.
10. World wide after sales service and technical support.

*Further details on the technical data sheet*



## Engine

Engine brand	FPT IVECO	
Engine model	C87TE4	
Cylinders	6	nr.
Speed	1500	r.p.m.
Cubic capacity	8.700	cm <sup>3</sup>
Air intake	Turbocharged	
Standard voltage	24 Vdc	Vdc
Optional voltage	Vdc	Vdc
Sae	1-14	
BMEP	0	kPa
Cooling	Water	

### ENGINE POWER

Flywheel P.R.P. Power	281.0	kW
Flywheel Stand-by Power	305.0	kW

### FUEL CONSUMPTION

Fuel Cons. at 100% (L.T.P.)	72.4 l/h
Fuel Cons. at 100% (P.R.P.)	72.9 l/h
Fuel Cons. at 75% (P.R.P.)	54.3 l/h
Fuel Cons. at 50% (P.R.P.)	37.6 l/h
Fuel Cons. at 25% (P.R.P.)	- l/h

### SPEED REGULATION

Electronic regulator	Standard
Precision class	-

### ENGINE DIMENSIONS AND LIQUIDS

Oil quantity	28.0 l
Antifreeze quantity	15.0 l
Radiator standard	IM50

### HEAT FROM ENGINE

Heat from radiator	202.0 kW
Heat from exhaust	238.0 kW
Heat from radiation	25.0 kW

### EXHAUST DATA

Exhaust temperature	488 °C
Cooling air flow	340.00 m <sup>3</sup> /min
Combustion air flow	18.10 m <sup>3</sup> /min
Exhaust gas flow	49.40 m <sup>3</sup> /min

### EMISSIONS

TA Luft	Not available
TA Luft/2	Not available
EPA	Not available
Stage	Not available

## Alternator

Alternator brand	STAMFORD
Alternator model	HCI4D
PRP Power	300.0 kVA
LTP Power	330.0 kVA

### ALTERNATOR WIRINGS

Connection	Series star
Phases	Three phases with neutral
Winding	12 terminals 50-60Hz Winding 311
Terminal Number	12 nr.

### ALTERNATOR PROTECTION

IP Protection	23
---------------	----

### VOLTAGE REGULATOR

Electronic regulator	AS440
Precision	1.0 ±%

## Baseframe

Model	GV150
Capacity	400 l

## Canopy & Silencer

Canopy model	GV150
Silencer model	MSR/a 125
Silencer outlet diameter	140.0 mm

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.