



## Performance

Continuous power (PRP)	600.0	(KVA)
Continuous power (PRP)	480.0	(KW)
Stand-by power (LTP)	660.0	(KVA)
Stand-by power (LTP)	528.0	(KW)
Power factor	0.8	

### VOLTAGE

Frequency (Hz)	50	Hz
Voltage (V)	400	V

### DIMENSIONS AND NOISE LEVEL

Width	1840	mm
Length	4500	mm
Height	2540	mm
Weight	5710	kg
Sound pressure 7 m.	74.0	dBA

## DATA REFERENCES

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0,850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.

**P.R.P. Prime Power-Continuous power at variable load:** The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer, according to ISO 8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.

**L.T.P. Limited-time running power-Limited power:** The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted.

*The data contained in this document is nominal and refers to the standard equipped model and is not binding. Psilos Services reserves the right to revise the information without notice per our policy of continuous product development and improvement.*



**GALAXY-P 600 GX**

## STRONG POINTS

1. Industrial diesel engine in genset version with certificate of origin.
2. Industrial brushless alternator with AVR.
3. Steel baseframe with retention basin and modular steel fuel tank with level sensor.
4. Soundproof canopy in galvanized, power coated sheet steel.
5. Soundproofing material made of high attenuation polyester fibre.
6. Internal exhaust silencer with insulated manifold.
7. Electrical panel mounted on board the unit with digital control device installed in metal box.
8. Compact for easy handling and use.
9. Test report, manuals and electrical drawings supplied.
10. World wide after sales service and technical support.

*Further details on the technical data sheet*



## Engine

Engine brand	PERKINS	
Engine model	2806C-E18TAG1A	
Cylinders	6	nr.
Speed	1500	r.p.m.
Cubic capacity	18.130	cm <sup>3</sup>
Air intake	Turbocharged	
Standard voltage	24 Vdc	Vdc
Optional voltage	Vdc	Vdc
Sae	0-18	
BMEP	2347	kPa
Cooling	Water	

### ENGINE POWER

Flywheel P.R.P. Power	523.0	kW
Flywheel Stand-by Power	574.0	kW

### FUEL CONSUMPTION

Fuel Cons. at 100% (L.T.P.)	134.0 l/h
Fuel Cons. at 100% (P.R.P.)	129.0 l/h
Fuel Cons. at 75% (P.R.P.)	96.0 l/h
Fuel Cons. at 50% (P.R.P.)	63.0 l/h
Fuel Cons. at 25% (P.R.P.)	- l/h

### SPEED REGULATION

Electronic regulator	Standard
Precision class	G3

### ENGINE DIMENSIONS AND LIQUIDS

Oil quantity	62.0 l
Antifreeze quantity	61.0 l
Radiator standard	IM50

### HEAT FROM ENGINE

Heat from radiator	150.0 kW
Heat from exhaust	480.0 kW
Heat from radiation	48.0 kW

### EXHAUST DATA

Exhaust temperature	550 °C
Cooling air flow	702.00 m <sup>3</sup> /min
Combustion air flow	40.00 m <sup>3</sup> /min
Exhaust gas flow	110.00 m <sup>3</sup> /min

### EMISSIONS

TA Luft	Not available
TA Luft/2	Not available
EPA	Not available
Stage	Stage 2

## Alternator

Alternator brand	MARELLI
Alternator model	MJB355MA4
PRP Power	610.0 kVA
LTP Power	665.0 kVA

### ALTERNATOR WIRINGS

Connection	Series star
Phases	Three phases with neutral
Winding	12 terminals 50-60Hz Winding 311
Terminal Number	12 nr.

### ALTERNATOR PROTECTION

IP Protection	23
---------------	----

### VOLTAGE REGULATOR

Electronic regulator	SX440
Precision	1.0 ±%

## Baseframe

Model	GV200
Capacity	1000 l

## Canopy & Silencer

Canopy model	GV200
Silencer model	MSR/a 150
Silencer outlet diameter	168.0 mm