



## Performance

Continuous power (PRP)	200.0	(KVA)
Continuous power (PRP)	160.0	(KW)
Stand-by power (LTP)	220.0	(KVA)
Stand-by power (LTP)	176.0	(KW)
Power factor	0.8	

### VOLTAGE

Frequency (Hz)	50	Hz
Voltage (V)	400	V

### DIMENSIONS AND NOISE LEVEL

Width	1110	mm
Length	2490	mm
Height	1790	mm
Weight	1700	kg
Sound pressure 7 m.	0.0	dBA

### DATA REFERENCES

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0,850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.

**P.R.P. Prime Power-Continuous power at variable load:** The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer, according to ISO 8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.

**L.T.P. Limited-time running power-Limited power:** The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted.

*The data contained in this document is nominal and refers to the standard equipped model and is not binding. Psilos Services reserves the right to revise the information without notice per our policy of continuous product development and improvement.*



**POWERFULL-F 201 B**

### STRONG POINTS

1. Industrial diesel engine in genset version with certificate of origin.
2. Industrial brushless alternator with AVR.
3. Large capacity steel baseframe-fuel tank with level sensor.
4. Industrial silencer and coupling flange.
5. Electrical panel mounted on board the unit with digital control device installed in metal box.
6. Compact for easy handling and use.
7. Test report, manuals and electrical drawings supplied.
8. World wide after sales service and technical support.

*Further details on the technical data sheet*



## Engine

Engine brand	FPT IVECO	
Engine model	N67TM7	
Cylinders	6	nr.
Speed	1500	r.p.m.
Cubic capacity	6.700	cm <sup>3</sup>
Air intake	Turbocharged	
Standard voltage	12 Vdc	Vdc
Optional voltage	24 Vdc	Vdc
Sae	3-11 1/2	
BMEP	2042	kPa
Cooling	Water	

### ENGINE POWER

Flywheel P.R.P. Power	176.5	kW
Flywheel Stand-by Power	195.0	kW

### FUEL CONSUMPTION

Fuel Cons. at 100% (L.T.P.)	49.0 l/h
Fuel Cons. at 100% (P.R.P.)	42.1 l/h
Fuel Cons. at 75% (P.R.P.)	35.1 l/h
Fuel Cons. at 50% (P.R.P.)	24.0 l/h
Fuel Cons. at 25% (P.R.P.)	0.0 l/h

### SPEED REGULATION

Electronic regulator	On Request
Precision class	G2

### ENGINE DIMENSIONS AND LIQUIDS

Oil quantity	17.2 l
Antifreeze quantity	10.5 l
Radiator standard	IM50

### HEAT FROM ENGINE

Heat from radiator	131.5 kW
Heat from exhaust	144.0 kW
Heat from radiation	26.0 kW

### EXHAUST DATA

Exhaust temperature	600 °C
Cooling air flow	228.00 m <sup>3</sup> /min
Combustion air flow	9.80 m <sup>3</sup> /min
Exhaust gas flow	32.20 m <sup>3</sup> /min

### EMISSIONS

TA Luft	Not available
TA Luft/2	Not available
EPA	Not available
Stage	Not available

## Alternator

Alternator brand	STAMFORD
Alternator model	UCI274H
PRP Power	200.0 kVA
LTP Power	220.0 kVA

### ALTERNATOR WIRINGS

Connection	Series star
Phases	Three phases with neutral
Winding	12 terminals 50-60Hz Winding 311
Terminal Number	12 nr.

### ALTERNATOR PROTECTION

IP Protection	23
---------------	----

### VOLTAGE REGULATOR

Electronic regulator	SX460
Precision	1.5 ±%

## Baseframe

Model	T2
Capacity	520 l

## Canopy & Silencer

Canopy model	SENZA COFANO
Silencer model	MS 15
Silencer outlet diameter	70.0 mm