



**STRONG POINTS**

1. TL-90 is the first lighting tower in the world with integrated vertical telescopic mast
2. Revolutionized the light tower market
3. Four powerful 1000W metal halide floodlights
4. High illumination in every working area
5. Extremely portable
6. Compact for easy handling and use
7. Test report, manuals and electrical drawings supplied
8. World wide after sales service and technical support

*Further details on the technical data sheet*

**Performance**

|                               |                              |                                                                                                                                          |
|-------------------------------|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Lifting System                | M:Manual / H:Hydraulic       | H                                                                                                                                        |
| Minimum Dimensions            | Length x Width x Height (cm) | 340 x 158 x 236                                                                                                                          |
| Maximum Dimensions            | Length x Width x Height (cm) | 340 x 185 x 850                                                                                                                          |
| Dry Weight                    | kg                           | 1150                                                                                                                                     |
| Lamps Power                   | W                            | 4 x 1000                                                                                                                                 |
| Illuminated Area (5 lux min.) | m <sup>2</sup>               | 4200                                                                                                                                     |
| Total Lumen                   | lm                           | 360 000                                                                                                                                  |
| Mast Rotation                 | °                            | 340                                                                                                                                      |
| Outlet Socket                 | -                            | 3 Kva - 230 V                                                                                                                            |
| Generator                     | -                            | 8 Kva - 230 V                                                                                                                            |
| Engine                        | -                            | Kubota D1105, Diesel, 3-cyl @150 rpm                                                                                                     |
| Cooling System                | -                            | Water                                                                                                                                    |
| Tank Capacity                 | liters                       | 112                                                                                                                                      |
| Total Running Time            | h                            | 60                                                                                                                                       |
| Noise Level                   | dB(A)@7m                     | 65                                                                                                                                       |
| Trailer                       | -                            | Road trailer with straight tow bar, brakes, lights and EU homologation with docs for registration                                        |
| Main Options Available        | -                            | Side-tow trailer, adjustable road trailer, special colors, hot deep zinc coating, auto start/stop system with timer and darkness control |

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.